

# UP25N(Z)



25 mm Ø, 3 mW - 300 W



## Key Features

- 1 **Modular Concept**  
Increase the power capability of your detector : 4 different cooling modules
- 2 **High Performance**
  - . Fast Rise Time (1.3 sec)
  - . High Damage Threshold (45 kW/cm<sup>2</sup>)
- 3 **Compact Design - Z Version**  
Only 60 mm x 60 mm front with 38 mm thick
- 4 **Energy Mode**  
Measure single shot energy up to 40 J
- 5 **High Quality Stand**  
Post threaded on both sides to allow extension
- 6 **Smart Interface**  
Containing all the calibration data

### See also

- . How it works .....14
- . Calibration .....6
- . Detailed dimensions .....75
- . Spectral absorption .....107
- . OEM Custom detectors .....80
- . Compatible monitors
  - SOLO 2 .....20
  - UNO .....22
  - S-LINK-2 .....24
  - P-LINK .....26



UP25N-40S-H9



UP25Z-15S-H9



## Accessories

### » Fiber Optic Adapters (FC, SMA, SC)

Variety of fiber adapter options to give you the most flexibility in using our power detectors with your fiber coupled lasers.



### » Extension Cables (4, 15, 20 and 25 m)

For some OEM, manufacturing and laboratory applications.









### » Pelican Carrying Case

We offer a robust hard shell polymer carrying case.



## SPECIFICATIONS

Models	UP25N-40S-H9	UP25N-100H-H9	UP25N-250F-H12	UP25N-300W-H9	UP25Z-15S-H9	UP25Z-200W-H9
						
Max Average Power (continuous)	40 W	100 W	250 W	300 W <sup>f</sup>	15 W	200 W <sup>f</sup>
Max Average Power (1 minute)	80 W	200 W	300 W	300 W <sup>f</sup>	30 W	200 W <sup>f</sup>

MEASUREMENT CAPABILITY	N-40S	N-100H	N-250F	N-300W	Z-15S	Z-200W
Spectral Range	0.19 – 20 $\mu\text{m}$	0.19 – 20 $\mu\text{m}$	0.19 – 20 $\mu\text{m}$	0.19 – 20 $\mu\text{m}$	0.19 – 20 $\mu\text{m}$	0.19 – 20 $\mu\text{m}$
Noise Equivalent Power <sup>a</sup>	3 mW	3 mW	10 mW	3 mW	3 mW	3 mW
Rise Time (nominal) <sup>b</sup>	1.3 sec	1.3 sec	1.3 sec	1.3 sec	1.3 sec	1.3 sec
Sensitivity (typ into 100 k $\Omega$ load) <sup>c</sup>	0.23 mV/W	0.23 mV/W	0.1 mV/W	0.23 mV/W	0.23 mV/W	0.23 mV/W
Calibration Uncertainty <sup>d</sup>	$\pm 2.5\%$	$\pm 2.5\%$	$\pm 2.5\%$	$\pm 2.5\%$	$\pm 2.5\%$	$\pm 2.5\%$
Repeatability	$\pm 0.5\%$	$\pm 0.5\%$	$\pm 0.5\%$	$\pm 0.5\%$	$\pm 0.5\%$	$\pm 0.5\%$
Energy Mode						
Sensitivity	0.14 mV/J	0.14 mV/J	0.05 mV/J	0.14 mV/J	0.14 mV/J	0.14 mV/J
Maximum Measurable Energy <sup>e</sup>	40 J	40 J	40 J	40 J	40 J	40 J
Noise Equivalent Energy <sup>a</sup>	0.2 J	0.2 J	0.2 J	0.2 J	0.2 J	0.2 J
Minimum Repetition Period	4.6 sec	4.6 sec	11.5 sec	4.6 sec	4.6 sec	4.6 sec
Maximum Pulse Width	123 ms	123 ms	390 ms	123 ms	133 ms	133 ms
Accuracy with energy calibration option	$\pm 5\%$	$\pm 5\%$	$\pm 5\%$	$\pm 5\%$	$\pm 5\%$	$\pm 5\%$

## DAMAGE THRESHOLDS

Maximum Average Power Density <sup>g</sup>	45 kW/cm <sup>2</sup>	45 kW/cm <sup>2</sup>	45 kW/cm <sup>2</sup>	45 kW/cm <sup>2</sup>	45 kW/cm <sup>2</sup>	45 kW/cm <sup>2</sup>
Pulsed Laser Damage Thresholds	Max Energy Density			Peak Power Density		
1064 nm, 360 $\mu\text{s}$ , 5 Hz	9 J/cm <sup>2</sup>			25 kW/cm <sup>2</sup>		
1064 nm, 7 ns, 10 Hz	1 J/cm <sup>2</sup>			143 MW/cm <sup>2</sup>		
532 nm, 7 ns, 10 Hz	0.6 J/cm <sup>2</sup>			86 MW/cm <sup>2</sup>		
266 nm, 7 ns, 10 Hz	0.3 J/cm <sup>2</sup>			43 MW/cm <sup>2</sup>		

## PHYSICAL CHARACTERISTICS

Effective Aperture Diameter	25 mm $\emptyset$	25 mm $\emptyset$	25 mm $\emptyset$	25 mm $\emptyset$	25 mm $\emptyset$	25 mm $\emptyset$
Absorber (High Damage Threshold)	H9	H9	H12	H9	H9	H9
Dimensions	89H x 89W x 32D mm	89H x 89W x 106D mm	89H x 89W x 116D mm	89H x 89W x 44D mm	60H x 60W x 38D mm	60H x 60W x 38D mm
Weight (head only)	0.68 kg	0.99 kg	1.44 kg	0.90 kg	0.33 kg	0.33 kg

## ORDERING INFORMATION

Full Product Name	UP25N-40S-H9	UP25N-100H-H9	UP25N-250F-H12	UP25N-300W-H9	UP25Z-15S-H9	UP25Z-200W-H9
Product Number (including stand)	200198	200202	201154	200210	200724	200726

a. Nominal value, actual value depends on electrical noise in the measurement system.

b. With Gentec-EO SOLO, UNO, P-LINK and S-LINK-2 monitors.

c. Maximum output voltage = sensitivity x maximum power.

d. Including linearity with power.

e. For 360  $\mu\text{s}$  pulses. Higher pulse energy possible when customized for long pulses (ms), less for short pulses (ns).

f. Minimum cooling flow 1 liters/min, water temperature  $\leq 22^\circ\text{C}$ , 1/8 NPT compression fittings for 1/4 inch semi-rigid tube. Contact Gentec-EO for clean deionized water cooling module option.

g. At 1064 nm, 10 W CW.

## America

Canada  
United States  
South America

## Europe

Austria  
Belgium  
France  
Germany  
Ireland  
Italy  
Poland  
Russia  
Spain  
Sweden  
Scandinavia  
Switzerland  
The Netherlands  
Turkey  
United Kingdom

## Asia Pacific

China  
India  
Indonesia  
Israel  
Japan  
Korea  
Malaysia  
Philippines  
Singapore  
Taiwan  
Thailand  
Vietnam

## Oceania

Australia  
New Zealand



Leader in Laser Beam Measurement Since 1972

### Headquarters

445 St-Jean-Baptiste, Suite 160  
Québec, QC, G2E 5N7, CANADA

T (418) 651-8003  
F (418) 651-1174  
1.888.5Gentec (543.6832)

[info@gentec-eo.com](mailto:info@gentec-eo.com)

### Calibration Centers

Quebec City, Canada  
Olching (Munich), Germany